

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.04.2024

Version number 12 (replaces version 11)

Revision: 10.04.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Hardener for 2K Epoxy Primer**

Article number: 88112, 88132

UFI: 40V7-M0D8-S00S-SUKG

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Priming
Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Storage: Store in a well-ventilated place. Keep cool.

Store in a well-ventilated place. Keep container tightly closed.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS05 GHS07 GHS08

Signal word

Danger

(Contd. on page 2)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.04.2024

Version number 12 (replaces version 11)

Revision: 10.04.2024

Trade name: Hardener for 2K Epoxy Primer

(Contd. of page 1)

· <u>Hazard-determining components of labelling:</u>	xylene butanol 1-methoxy-2-propanol ethylbenzene
· <u>Hazard statements</u>	H226 Flammable liquid and vapour. H315 Causes skin irritation. H318 Causes serious eye damage. H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. H373 May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.
· <u>Precautionary statements</u>	H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects. P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read carefully and follow all instructions. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe mist/vapours/spray. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 Do NOT induce vomiting. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER/doctor if you feel unwell. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
· 2.3 Other hazards	The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.
· Results of PBT and vPvB assessment	
· PBT:	Not applicable.
· vPvB:	Not applicable.
· <u>Determination of endocrine-disrupting properties</u>	For information on endocrine disrupting properties see section 11.

SECTION 3: Composition/information on ingredients**3.2 Mixtures**· Description: Mixture: consisting of the following components.· Dangerous components:

CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119555267-33 01-2119488216-32	xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	25-50%
--	---	--------

(Contd. on page 3)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.04.2024

Version number 12 (replaces version 11)

Revision: 10.04.2024

Trade name: Hardener for 2K Epoxy Primer

(Contd. of page 2)

CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3 Reg.nr.: 01-2119457435-35 02-2119752510-47-0000	1-methoxy-2-propanol Flam. Liq. 3, H226 STOT SE 3, H336	25-50%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35 01-2119892111-44	ethylbenzene Flam. Liq. 2, H225 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H332 Aquatic Chronic 3, H412	1-5%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	butanol Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-5%
CAS: 445498-00-0 EC number: 610-196-5	Formaldehyde, polymer with N1,N1-dimethyl-1,3-propanediamine and phenol Aquatic Chronic 2, H411 Acute Tox. 4, H302	1-5%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	1-5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident. Position and transport stably in side position.
- After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Headache
Dizziness
Dizziness

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 4)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.04.2024

Version number 12 (replaces version 11)

Revision: 10.04.2024

Trade name: Hardener for 2K Epoxy Primer

(Contd. of page 3)

- For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** In case of fire, the following can be released:
Carbon monoxide (CO)
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- Protective equipment: Mount respiratory protective device.
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.
Cool endangered receptacles with water spray.
- Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.
Ensure adequate ventilation
Use respiratory protective device against the effects of fumes/dust/aerosol.
- **6.2 Environmental precautions:** Do not allow to penetrate the ground/soil.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
- Information about fire - and explosion protection: Fumes can combine with air to form an explosive mixture.
Do not spray onto a naked flame or any incandescent material.
Use explosion-proof apparatus / fittings and spark-proof tools.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.04.2024

Version number 12 (replaces version 11)

Revision: 10.04.2024

Trade name: Hardener for 2K Epoxy Primer

(Contd. of page 4)

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by****storerooms and receptacles:****Information about storage in one
common storage facility:**

Prevent any seepage into the ground.

VCI-Konzept für die Zusammenlagerung von Chemikalien beachten.

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

**Further information about storage
conditions:**

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Protect from frost.

Keep container tightly sealed.

Storage class:

3

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****107-98-2 1-methoxy-2-propanol**

IOELV	Short-term value: 568 mg/m ³ , 150 ppm
	Long-term value: 375 mg/m ³ , 100 ppm
	Skin

100-41-4 ethylbenzene

IOELV	Short-term value: 884 mg/m ³ , 200 ppm
	Long-term value: 442 mg/m ³ , 100 ppm
	Skin

123-86-4 n-butyl acetate

IOELV	Short-term value: 723 mg/m ³ , 150 ppm
	Long-term value: 241 mg/m ³ , 50 ppm

DNELs**1330-20-7 xylene**

Oral	DNEL (Langzeit-wiederholt)	12.5 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	212 mg/kg bw/day (ARB)
		125 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	442 mg/m ³ Air (ARB)
		260 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	221 mg/m ³ Air (ARB)
		65.3 mg/m ³ Air (BEV)

107-98-2 1-methoxy-2-propanol

Oral	DNEL (Langzeit-wiederholt)	33 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	183 mg/kg bw/day (ARB)
		78 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	553.5 mg/m ³ Air (ARB)
	DNEL (Langzeit-wiederholt)	369 mg/m ³ Air (ARB)
		43.9 mg/m ³ Air (BEV)

100-41-4 ethylbenzene

Oral	DNEL (Langzeit-wiederholt)	1.6 mg/kg bw/day (BEV)
------	----------------------------	------------------------

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.04.2024

Version number 12 (replaces version 11)

Revision: 10.04.2024

Trade name: Hardener for 2K Epoxy Primer

(Contd. of page 5)

Dermal	DNEL (Langzeit-wiederholt)	180 mg/kg bw/day (ARB)
Inhalative	DNEL (Kurzzeit-akut)	293 mg/m ³ Air (ARB)
	DNEL (Langzeit-wiederholt)	77 mg/m ³ Air (ARB)
		15 mg/m ³ Air (BEV)

71-36-3 butanol

Oral	DNEL (Langzeit-wiederholt)	1,562 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	3,125 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	310 mg/m ³ Air (ARB)
		155 mg/m ³ Air (BEV)

123-86-4 n-butyl acetate

Oral	DNEL (Kurzzeit-akut)	2 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	2 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	11 mg/kg bw/day (ARB)
		6 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	11 mg/kg bw/day (ARB)
		6 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	600 mg/m ³ Air (ARB)
		300 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	48-300 mg/m ³ Air (ARB)
		12-35.7 mg/m ³ Air (BEV)

· PNECs**1330-20-7 xylene**

PNEC (wässrig)	6.58 mg/l (KA)
	0.327 mg/l (MW)
	0.327 mg/l (SW)
	0.327 mg/l (WAS)
PNEC (fest)	2.31 mg/kg Trockengew (BO)
	12.46 mg/kg Trockengew (MWS)
	12.46 mg/kg Trockengew (SWS)

107-98-2 1-methoxy-2-propanol

PNEC (wässrig)	100 mg/l (KA)
	1 mg/l (MW)
	10 mg/l (SW)
	100 mg/l (WAS)
PNEC (fest)	2.47 mg/kg Trockengew (BO)
	4.17 mg/kg Trockengew (MWS)
	41.6 mg/kg Trockengew (SWS)

100-41-4 ethylbenzene

PNEC (wässrig)	9.6 mg/l (KA)
	0.01 mg/l (MW)
	0.1 mg/l (SW)
	0.1 mg/l (WAS)
PNEC (fest)	2.68 mg/kg Trockengew (BO)
	1.37 mg/kg Trockengew (MWS)
	13.7 mg/kg Trockengew (SWS)

(Contd. on page 7)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.04.2024

Version number 12 (replaces version 11)

Revision: 10.04.2024

Trade name: Hardener for 2K Epoxy Primer

(Contd. of page 6)

71-36-3 butanol

PNEC (wässrig)	2,476 mg/l (KA)
	0.008 mg/l (MW)
	0.082 mg/l (SW)
	2.25 mg/l (WAS)
PNEC (fest)	0.0166 mg/kg Trockengew (BO)
	0.0324 mg/kg Trockengew (MWS)
	0.324 mg/kg Trockengew (SWS)

123-86-4 n-butyl acetate

PNEC (wässrig)	35.6 mg/l (KA)
	0.018 mg/l (MW)
	0.18 mg/l (SW)
	0.36 mg/l (WAS)
PNEC (fest)	0.0903 mg/kg Trockengew (BO)
	0.0981 mg/kg Trockengew (MWS)
	0.981 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.

· **8.2 Exposure controls**

- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.
 Use skin protection cream for skin protection.
 Clean skin thoroughly immediately after handling the product.
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Do not inhale gases / fumes / aerosols.
 Avoid contact with the eyes and skin.
 Store protective clothing separately.

· Respiratory protection:

Short term filter device:
 Filter A-P2
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
 Preventive skin protection by use of skin-protecting agents is recommended.
 After use of gloves apply skin-cleaning agents and skin cosmetics.

· Hand protection

**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Fluorocarbon rubber (Viton)
 Nitrile rubber, NBR
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 8)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.04.2024

Version number 12 (replaces version 11)

Revision: 10.04.2024

Trade name: Hardener for 2K Epoxy Primer

(Contd. of page 7)

- Penetration time of glove material Value for the permeation: Level ≤ 6
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
Vitoject (KCL, Art_No. 890)
Butyl rubber, BR
- As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR
Camatril (KCL, 730, 731, 732, 733)
Butoject (KCL, Art_No. 897, 898)
Butyl rubber, BR
- Not suitable are gloves made of the following materials: Leather gloves
Strong material gloves
- Eye/face protection  Tightly sealed goggles
- Body protection: Protective work clothing

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

- General Information
- Colour: Amber coloured
- Odour: Amine-like
- Odour threshold: Not determined.
- Melting point/freezing point: Undetermined.
- Boiling point or initial boiling point and boiling range 116-118 °C
- Flammability Not applicable.
- Lower and upper explosion limit
- Lower: 1.1 Vol % (107-98-2 1-methoxy-2-propanol)
- Upper: ~20 Vol % (107-98-2 1-methoxy-2-propanol)
- Flash point: 23 °C
- Auto-ignition temperature: 270 °C (107-98-2 1-methoxy-2-propanol)
- Decomposition temperature: Not determined.
- pH Not determined.
Not applicable
- Viscosity:
- Kinematic viscosity at 40 °C <20 mm²/s
- Dynamic: Not determined.
- Solubility
- water: Not miscible or difficult to mix.
- Partition coefficient n-octanol/water (log value) Not determined.
- Vapour pressure at 20 °C: 12 hPa (107-98-2 1-methoxy-2-propanol)
- Density and/or relative density
- Density at 20 °C: 0.94 g/cm³
- Relative density Not determined.
- Vapour density Not determined.

(Contd. on page 9)

EU

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.04.2024

Version number 12 (replaces version 11)

Revision: 10.04.2024

Trade name: Hardener for 2K Epoxy Primer

(Contd. of page 8)

9.2 Other information

- Appearance:
- Form: Fluid
- Important information on protection of health and environment, and on safety.
- Ignition temperature: Product is not selfigniting.
- Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- Solvent content:
- Organic solvents: 69.1 %
- Solids content: 28.0 %
- Change in condition
- Evaporation rate Not determined.

- Information with regard to physical hazard classes
- Explosives Void
- Flammable gases Void
- Aerosols Void
- Oxidising gases Void
- Gases under pressure Void
- Flammable liquids Flammable liquid and vapour.
- Flammable solids Void
- Self-reactive substances and mixtures Void
- Pyrophoric liquids Void
- Pyrophoric solids Void
- Self-heating substances and mixtures Void
- Substances and mixtures, which emit flammable gases in contact with water Void
- Oxidising liquids Void
- Oxidising solids Void
- Organic peroxides Void
- Corrosive to metals Void
- Desensitised explosives Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Forms explosive gas mixture with air.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:**ATE (Acute Toxicity Estimates)**

Oral	LD50	15,000-100,000 mg/kg (rat)
------	------	----------------------------

(Contd. on page 10)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.04.2024

Version number 12 (replaces version 11)

Revision: 10.04.2024

Trade name: Hardener for 2K Epoxy Primer

(Contd. of page 9)

Inhalative	LC50/4 h	430 mg/l (rat)
------------	----------	----------------

1330-20-7 xylene

Oral	LD50	3,523-4,300 mg/kg (rat)
Dermal	LD50	>4,200 mg/kg (rabbit)
Inhalative	LC50/4h	29,000 mg/m3 (rat)
	LC50/4 h	21.7 mg/l (rat)
	LC50/48h	86 mg/l (Leuciscus idus)

107-98-2 1-methoxy-2-propanol

Oral	LD50	4,016 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
		13,500 mg/kg (rabbit)
Inhalative	LC50	27.596 mg/l (rat)
	LC50/4 h	54.6 mg/l (rat)

100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/l (rat)

71-36-3 butanol

Oral	LD50	3,430 mg/kg (rabbit) (OECD 402)
		2,292 mg/kg (rat) (OECD 401)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4h	17.76 mg/m3 (rat)
	LC50/4 h	8,000 mg/l (rat)

445498-00-0 Formaldehyde, polymer with N1,N1-dimethyl-1,3-propanediamine and phenol

Oral	LD50	300-2,000 mg/kg (rat)
------	------	-----------------------

123-86-4 n-butyl acetate

Oral	LD50	10,760 mg/kg (rat) (OECD 423)
Dermal	LD50	>14,112 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4 h	23.4 mg/l (rat) (OECD 403)
	LC50	390 mg/m3 (rat)
	LC50/48h	64 mg/l (Brachydanio rerio)

- | | |
|-------------------------------------|---|
| · Skin corrosion/irritation | Causes skin irritation. |
| · Serious eye damage/irritation | Causes serious eye damage. |
| · Respiratory or skin sensitisation | Based on available data, the classification criteria are not met. |
| · Germ cell mutagenicity | Based on available data, the classification criteria are not met. |
| · Carcinogenicity | Based on available data, the classification criteria are not met. |
| · Reproductive toxicity | Based on available data, the classification criteria are not met. |
| · STOT-single exposure | Based on available data, the classification criteria are not met. |
| · STOT-repeated exposure | Based on available data, the classification criteria are not met. |
| · Aspiration hazard | Based on available data, the classification criteria are not met. |

11.2 Information on other hazards

- Endocrine disrupting properties

None of the ingredients is listed.

(Contd. on page 11)

EU

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.04.2024

Version number 12 (replaces version 11)

Revision: 10.04.2024

Trade name: Hardener for 2K Epoxy Primer

(Contd. of page 10)

SECTION 12: Ecological information**· 12.1 Toxicity****· Aquatic toxicity:****1330-20-7 xylene**

EC50/24h	>175 mg/l (bacteria)
	165 mg/l (daphnia magna)
EC50	10 mg/l (bacteria)
IC50	96 mg/l (BES)
	1 mg/l (daphnia magna)
LC50	2 mg/l (piscis)
LC50/24h	32 mg/l (Iepomis macrochirus)
IC50/72h	2.2 mg/l (algae)
	3.3 mg/l (Pseudokirchneriella subcapitata)
EC50/48h	3.82 mg/l (daphnia magna)
NOEC	0.96-1.17 mg/l (daphnia magna)
	>1.3 mg/l (Oncorhynchus mykiss)
	0.44 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EC50/72h	4.7 mg/l (Pseudokirchneriella subcapitata)
	2.2 mg/l (Selenastrum capricornutum) (OECD 201)
LC50/96h	16.9 mg/l (carp)
	1.57 mg/l (Cyprinus carpio)
	3.77-13.5 mg/l (piscis)
	20.9 mg/l (Iepomis macrochirus)
	7.6 mg/l (Oncorhynchus mykiss)
	13.4 mg/l (Pimephales promelas)

107-98-2 1-methoxy-2-propanol

EC50/96h	>1,000 mg/l (BES)
	>1,000 mg/l (Pseudokirchneriella subcapitata)
EC50	>1,000 mg/l (BES) (OECD 209)
	>1,000 mg/l (Pseudokirchneriella subcapitata)
LC 0/96h	>4,600 mg/l (Leuciscus idus)
EC50/48h	21,100-25,900 mg/l (daphnia magna)
LC50/96h	>100 mg/l (daphnia magna)
	>100 mg/l (Desmodesmus subspicatus)
	4,600-10,000 mg/l (Leuciscus idus) (DIN 38412)
	>1,000 mg/l (Oncorhynchus mykiss) (OECD 203)
	20,800 mg/l (Pimephales promelas) (ASTM)

100-41-4 ethylbenzene

LC50/24h	26.74-43.67 mg/l (Iepomis macrochirus)
EC5	12 mg/l (Pseudomonas putida)
EC50/48h	1.8-2.4 mg/l (daphnia magna)
EC50/16h	>12 mg/l (bacteria)
EC50/30min	600 mg/l (BES)
EC50/72h	4.9 mg/l (Skeletonema costatum (Kieselalge))

(Contd. on page 12)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.04.2024

Version number 12 (replaces version 11)

Revision: 10.04.2024

Trade name: Hardener for 2K Epoxy Primer

(Contd. of page 11)

LC50/96h	5.4 mg/l (Pseudokirchneriella subcapitata) 4.6 mg/l (selenastrum capricornutum) 94.44 mg/l (carp) 32 mg/l (Iepomis macrochirus) 4.2 mg/l (Oncorhynchus mykiss) 12.1 mg/l (pimephales promelas)
----------	---

71-36-3 butanol

EC50/96h	225 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EC50	4,400 mg/l (pseudomonas putida)
IC50/72h	>500 mg/l (Desmodesmus subspicatus)
EC10/16h	2,376 mg/l (pseudomonas putida) (DIN 38412)
NOEC/21d	4.1 mg/l (daphnia magna) (OECD 211)
EC50/48h	1,328 mg/l (daphnia magna) (OECD 202)
EC50/72h	8,500 mg/l (algae)
LC50/96h	1,200 mg/l (Leuciscus idus) 1,376 mg/l (pimephales promelas) (OECD 203) >500 mg/l (Scenedesmus subspicatus)

445498-00-0 Formaldehyde, polymer with N1,N1-dimethyl-1,3-propanediamine and phenol

EC50/48h	24 mg/l (daphnia magna)
EC50/72h	>219 mg/l (selenastrum capricornutum)
LC50/96h	40 mg/l (Brachydanio rerio)

123-86-4 n-butyl acetate

EC50/24h	72.8 mg/l (daphnia magna) (DIN 38412)
EC50/96h	320 mg/l (algae)
LC50/24h	205 mg/l (daphnia magna)
IC50/72h	648 mg/l (Desmodesmus subspicatus)
EC10/18h	959 mg/l (pseudomonas putida)
EC50/48h	44 mg/l (daphnia magna) (OECD 202)
EC50/16h	959 mg/l (pseudomonas putida)
NOEC	200 mg/kg (Desmodesmus subspicatus)
NOEC/21d	23 mg/l (daphnia magna) (OECD 211)
EC50/72h	647.7 mg/l (Desmodesmus subspicatus) (Zellvermehrungshemmtest) 397 mg/l (Scenedesmus subspicatus)
LC50/96h	62 mg/l (Danio rerio.) 81 mg/l (piscis) 100 mg/l (Iepomis macrochirus) 62 mg/l (Leuciscus idus) (DIN 38412) 18 mg/l (pimephales promelas) (OECD 203)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· PBT: Not applicable.

· vPvB: Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 13)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.04.2024

Version number 12 (replaces version 11)

Revision: 10.04.2024

Trade name: Hardener for 2K Epoxy Primer

(Contd. of page 12)

· **12.7 Other adverse effects**· Additional ecological information:· General notes:

Do not allow product to reach ground water, water course or sewage system.
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

SECTION 13: Disposal considerations· **13.1 Waste treatment methods**· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

· Uncleaned packaging:· Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.
Disposal must be made according to official regulations.

* **SECTION 14: Transport information**· **14.1 UN number or ID number**· ADR, IMDG, IATA

UN1263

· **14.2 UN proper shipping name**· ADR

1263 PAINT RELATED MATERIAL

· IMDG, IATA

PAINT RELATED MATERIAL

· **14.3 Transport hazard class(es)**· ADR· Class

3 (F1) Flammable liquids.

· Label

3

· IMDG, IATA· Class

3 Flammable liquids.

· Label

3

· **14.4 Packing group**· ADR, IMDG, IATA

III

· **14.5 Environmental hazards:**

Not applicable.

· **14.6 Special precautions for user**

Warning: Flammable liquids.

· Hazard identification number (Kemler code):

30

(Contd. on page 14)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.04.2024

Version number 12 (replaces version 11)

Revision: 10.04.2024

Trade name: Hardener for 2K Epoxy Primer

(Contd. of page 13)

· EMS Number:	F-E,S-E
· Segregation groups	(SGG6) Cyanides
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Directive 2012/18/EU	
· Named dangerous substances - ANNEX I	None of the ingredients is listed.
· Seveso category	P5c FLAMMABLE LIQUIDS
· Qualifying quantity (tonnes) for the application of lower-tier requirements	5,000 t
· Qualifying quantity (tonnes) for the application of upper-tier requirements	50,000 t
· REGULATION (EC) No 1907/2006 ANNEX XVII	Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

(Contd. on page 15)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 10.04.2024

Version number 12 (replaces version 11)

Revision: 10.04.2024

Trade name: Hardener for 2K Epoxy Primer

(Contd. of page 14)

- National regulations:
- Information about limitation of use: Employment restrictions concerning pregnant and lactating women must be observed.
Employment restrictions concerning juveniles must be observed.
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- Substances of very high concern (SVHC) according to REACH, Article 57
- None of the ingredients is listed.
- VOC EU 650.9 g/l
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

- Department issuing SDS: Laboratory
- Date of previous version: 19.10.2022
- Version number of previous version: 11
- Abbreviations and acronyms:
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - ICAO: International Civil Aviation Organisation
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - DNEL: Derived No-Effect Level (REACH)
 - PNEC: Predicted No-Effect Concentration (REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - SVHC: Substances of Very High Concern
 - vPvB: very Persistent and very Bioaccumulative
 - ATE: Acute toxicity estimate values
 - Flam. Liq. 2: Flammable liquids – Category 2
 - Flam. Liq. 3: Flammable liquids – Category 3
 - Acute Tox. 4: Acute toxicity – Category 4
 - Skin Irrit. 2: Skin corrosion/irritation – Category 2
 - Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 - STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 - Asp. Tox. 1: Aspiration hazard – Category 1
 - Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 - Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

EU