



Made under

ISO 14001

ISO 9001

>> Type of use (*)

Thanks to its technical features, this glove is particularly suitable for all light works requiring good dexterity as well as good resistances in oily and / or fatty environments: automobile assembly, automobile repair, construction, public works, raw material handling, deep sea fishing, maintenance of public parks, painting, industrial maintenance, carpentry...

>> General features

- ✓ **Construction, materials:** cut and sewn pattern. 100% interlock cotton liner. Light nitrile coating. Open back version. Knitted wrist. **With Actifresh®.**
- ✓ **Colour:** natural colour liner / blue coating.
- ✓ **Sizes:** 7, 8, 9, 10.
- ✓ **Packing:** - Cartons of 100 pairs.
- Bundles of 10 pairs.



Learn more: www.singer.fr

Fine
work in a
damp
environment

>> Advantages

- ✓ The guarantee of **ISO 9001** manufacturing
 - ✓ Cotton interlock liner: brings the comfort of a natural material which facilitates the absorption of perspiration.
 - ✓ The light coating provides a good softness for light handling works and offers a good grip.
 - ✓ The back of the glove uncoated will allow the hand to breathe.
 - ✓ Anti-bacterial effect of the **Actifresh®** treatment deprives bacteria from developing and growing.
- The **Actifresh®** treatment is effective against bacteria, fungi, rust, stains and algae in preventing these micro-organisms from developing. It promotes a longer life and avoids the creation of bad odours.
- ✓ Knitted wrist for a snug fit.

>> Conformity

This glove has been tested according to the following European standards :


- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanical risks.



It complies with **European Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**

EU type examination certificate (module B) issued by **SATRA (Ireland)**, notified body **n°2777**.

EN 388: 2016. Protective gloves against mechanical risks

Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Levels ▼	EN 388 : 2016  3 1 1 1 X
Abrasion resistance (number of cycles)	100	500	2000	8000	-	3	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	1	
Tear resistance (in Newtons)	10	25	50	75	-	1	
Perforation resistance (in Newtons)	20	60	100	150	-	1	
Cut resistance (N) (as per EN ISO13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Level
	2	5	10	15	22	30	X

«X» means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**

SINGER®
safety