



>> Type of use (\*)

Thanks to its technical characteristics, this glove is particularly suitable for all major works requiring dexterity and an high touch as well. It protects also against low mechanical risks, especially abrasion.

Automotive industry; precision engineering; Industrial maintenance, electronic industry, small parts assembly, laboratories, goldsmith's trade, clean rooms, photography, precision engineering.

>> Technical features

- ✓ **Construction:** Seamless knitted liner. PU coated finger tips. Open back (ventilated). Elasticated knitted wrist.
- ✓ Polyamid fibres.
- ✓ **Gauge:** 13
- ✓ **Colour:** white.
- ✓ **Sizes:** 6, 7, 8, 9, 10.
- ✓ **Packing:** - carton of 100 pairs.  
- bundle of 10 pairs.



Learn more: [www.singer.fr](http://www.singer.fr)

Fine work  
in a dry  
environment



>> Advantages

- ✓ Outstanding fit, flexibility and feel.
- ✓ The soft seamless liner provides exceptional comfort, reduces hand fatigue and will not irritate hand even during long periods of wear.
- ✓ Elasticated knitted wrist for a snug fit.
- ✓ The back of the glove uncoated allowing the hand to breathe.
- ✓ P.V.C dotted palm: excellent grip in dry conditions for safe and secure handling of small parts and tools or fine handling tasks.
- ✓ **ISO 9001** certification for a regular and good quality of products.

>> Conformity

This glove has been tested according to the following European standards :

- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanicals risks.



It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**

EU type examination certificate (module B) issued by the **CTC**. Notified body n°0075.

Download the EU declaration of conformity on: <http://docs.singer.fr>

**EN 388: 2016. Protective gloves against mechanical risks**

Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Levels ▼	<b>EN 388 : 2016</b>  <b>0 1 3 X X</b>
Abrasion resistance (number of cycles)	100	500	2000	8000	-	<b>0</b>	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	<b>1</b>	
Tear resistance (in Newtons)	10	25	50	75	-	<b>3</b>	
Perforation resistance (in Newtons)	20	60	100	150	-	<b>X</b>	
Cut resistance (N) As per EN ISO13997) (TDM test) «X» means that the glove has not been submitted to the test.	Level A	Level B	Level C	Level D	Level E	Level F	Level
	2	5	10	15	22	30	<b>X</b>

Your distributor **SINGER® SAFETY**

