


90 g



[Curved shape]



>> Type of uses (*)

Thanks to its technical characteristics, this device is particularly suitable for all major works requiring protection against mechanical risks, liquid splashes namely: industry, mechanical workshops, scouring, automotive industry, agriculture, forestry development, facade renovation, work in a quarry, carpentry, maintenance of parks and gardens, painting, laboratory...

>> Technical features

Quality safety goggle.
P.V.C frame with direct ventilation.
Panoramic clear anti-scratch and anti-fog polycarbonate curved lens.
Quick adjustable elastic headband.

- ✓ Lens thickness 2.00 mm.
- ✓ Weight : 90 g.
- ✓ Dimensions:
 - Nose bridge width : 4.50 cm.
 - Nose bridge height : 3.50 cm.
 - Overall height : 8.50 cm.
 - Overall width : 16.50 cm (hinge to hinge).
- ✓ Packing : - Carton of 10 goggles.
 - Box of 10 goggles.
 - Each goggle packed under individual polybag.



Learn more www.singer.fr

>> Advantages

- ✓ The curved shape of this goggle provides a perfect fit of the equipment to all faces for a better comfort, less fatigue and wide vision.
- ✓ Extra-wide and adjustable elastic headband for more comfort and secure fit.
- ✓ Peripheral vision.
- ✓ Reliability of an ISO 9001 system in production.



>> Conformity

This product has been tested according to the following European Standard:

- ✓ **EN 166: 2001.** Personal eye-protection. Specifications.

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**

EU type examination certificate (**module B**) issued by **BSI (Netherlands)**. Notified body **n°2797**.

Download the EU declaration of conformity on: <http://docs.singer.fr>



Mechanical protection	Symbole BT	Impact resistant against high speed particles at high temperatures (corresponds to the impact of a steel ball with a diameter of 0.86g launched at 120 m/s).
Optical quality	Symbole 1	Class 1 continuous works (better quality).
Scale number	Symbole 9 Symbole 3 Symbole 4	Molten metal and hot solids. Liquids. Large dust particles (> 5um).

Your distributor **SINGER® SAFETY**

