TEAMGROUP EX2 SSD

Primary functions and features

- Optimized performance
- Blazing read/write speed
- **Complete lineup of capacities**
- Trustworthy reliability

Ordering information

Capacity	Team P/N
512GB	T253E2512G0C101
1TB	T253E2001T0C101
2TB	T253E2002T0C101
8TB	T253E2008T0C101
16TB	T253E2016T0C101

TEAMGROUP

Specifications

Interface	SATA III 6Gb/s
Capacity	512GB / 1TB / 2TB / 8TB / 16TB[1]
Voltage	DC +5V
Operation Temperature	0°C ~ 70°C
Storage Temperature	-40°C ~ 85°C
Terabyte Written	512GB : 120TBW 1TB : 200TBW 2TB : 400TBW 8TB : 2000TBW 16TB : 4000TBW[2]
Performance	Crystal Disk Mark : Read/Write : up to 550/520 MB/s[3]
Dimensions	100(L) x 69.9(W) x 7 (H) mm
Humidity	0°C ~ 55°C / 5% ~ 95% RH,non-condensing
Vibration	20G (non-operating)
Shock	1500G
MTBF	1,000,000 Hours
Operating System	• Windows 11 / 10 / 8.1 / 8 / 7 • MAC OS 10.4 or later • Linux 2.6.33 or later
Warranty	3-year limited warranty

[1] 1GB=1,000,000,000 Bytes. In OS system, it would be displayed as 1,000,000,000 Bytes/1024/1024/1024 = 0.93GB
[2] Definition and conditions of TBW (Terabytes Written)are based on JEDEC standard.
[3] Transmission speed will vary according to different hardware/software conditions, therefore the data can only use for basic reference.
※We reserve the right to modify product specifications without prior notice. Different devices may have a different best format for usage. It is recommended to format the device before use to ensure the correctness and the integrity of the SSD.