# T-FORCE DELTA RGB DDR5 GAMING DESKTOP MEMORY

Primary functions and features

- RGB Colors & 120°Ultra-Wide Lighting
- Supports Intel XMP3.0 for One-Click Overclocking
- Power Management IC (PMIC) Equipped for Stable, Efficient Power Usage
- Strengthened PMIC Cooling Design
- On-die ECC for Stable System
- High-Quality ICs Selected for Stability & Reliability
- Equipped with Smart RGB IC Controller that Supports Various
- Lighting Effect Software
- Innovative circuit structure design lowering power consumption and heat

  (Invention patent number in Taiwan: I842298)

  (Invention patent number in the US: US12111715B2)

Specifications

Module Type	DDR5 288 Pin Non-ECC Unbuffered DIMM						
Frequency	8200	8000	8000	7800	7600	7600	7200
Capacity	2x24GB	2x16GB	2x24GB	2x16GB	2x16GB	2x24GB	2x16GB 2x24GB
Latency	38-49-49-84	38-48-48-84	38-49-49-84	38-48-48-84	36-46-46-84	36-47-47-84	34-42-42-84
Data Transfer Bandwidth	65,600 MB/s (PC5 65600)	64,000 MB/s (PC5-64000)	64,000 MB/s (PC5-64000)	62,400 MB/s (PC5-62400)	60,800 MB/s (PC5 60800)	60,800 MB/s (PC5 60800)	57,600 MB/s (PC5 57600)
Voltage	1.4V	1.45V	1.4V	1.4V	1.4V	1.4V	1.4V
Compatibility	Intel: 700 series						
Dimensions	46.1(H) x 144.2(L) x 7(W)mm						
Profile	8200 MHz↑ Intel XMP 3.0 8000 MHz↓ Intel XMP 3.0 / AMD EXPO						
Warranty	Lifetime warranty						

Module Type	DDR5 288 Pin Non-ECC Unbuffered DIMM						
Frequency	7000	7000	6800	6800	6600	6400	6400	6400
Capacity	16GB 2x16GB	2x16GB 2x48GB	2x16GB	2x48GB	2x16GB	16GB 2x16GB	2x48GB	16GB 2x16GB 2x24GB
Latency	32-42-42-84	34-42-42-84	34-44-44-84	36-46-46-84	34-40-40-84	30-39-39-76	32-39-39-84	32-39-39-84
Data Transfer Bandwidth	56,000 MB/s (PC5 56000)	56,000 MB/s (PC5 56000)	54,400 MB/s (PC5 54400)	54,400 MB/s (PC5 54400)	52,800 MB/s (PC5 52800)	51,200 MB/s (PC5 51200)	51,200 MB/s (PC5 51200)	51,200 MB/s (PC5 51200)
Voltage	1.4V	1.4V	1.4V	1.4V	1.4V	1.35V	1.4V	1.35V
Compatibility	Intel: 700 series						
Dimensions	46.1(H) x 144.2(L) x 7(W)mm						
Profile	8200 MHz↑ Intel XMP 3.0 8000 MHz↓ Intel XMP 3.0 / AMD EXPO						
Warranty	Lifetime warranty						

T-FORCE

T-FORCE is TEAM force. The red "T" on the logo of "TF" represents TEAMGROUP's passion for the storage products. The black "F" represents TEAMGROUP's over 18 years of promotion of storage products. The visual design of the perfect combination elegantly symbolizes a pair of flying wings.

TEAM GROUP

T·CREATE

PERFECT CHOICE

Products from Team Group Inc. have been well received by the technology media around the globe and have won honors such as COMPUTEX d&i awards, COMPUTEX Best Choice Award, GOOD DESIGN AWARD, Golden Pin Design Award, Taiwan Excellence Awards, iF Design Award and Red Dot Award.

GLOBALIZATION

Team Group Inc. has built up a strong center in Taiwan for production, R&D, sales and customer service, and has over 300 global sales agents and 400 employees worldwide. Team Group Inc. uses differentiating sales strategies with a global vision and localized channel management to establish a closed distribution network.

GUARANTEED QUALITY & WARRANTY SERVICE

Team Group Inc. is well praised by the industry and customers by adhering to the corporate philosophy of "Integrity, Innovation, Professionalism, Efficiency, Discipline, and Simplicity." We offer faster repair and exchange services than others, guaranteeing a minimized delivery time for every global customer.

SOLID R&D CAPABILITIES

With the best technical and manufacturing team, products from Team Group Inc. are made with innovation and strict quality control. Our memory technology has passed the ISO9001 and ISO14001 certifications, taking the lead in the memory industry with our latest overclocking memory modules.

3F., No.166, Jian 1st Rd., Zhonghe Dist.,New Taipei City 23511, Taiwan
Team Group Inc.
Tel: +886-2-82265000 Fax: +886-2-82265808
mail: sales@teamgroup.com.tw / rma@teamgroup.com.tw

CAN ICES-3(B)/NMB-3(B)

Module Type	DDR5 288 Pin Non-ECC Unbuffered DIMM							
Frequency	6400	6400	6400	6400	6400	6400	6200	6000
Capacity	16GB 2x16GB	2x32GB	32GB 2x32GB	2x16GB	2x16GB	8GB 16GB 2x8GB 2x16GB	16GB 2x16GB	16GB 2x16GB
Latency	34-39-39-76	34-44-44-84	34-46-46-84	38-46-46-76	38-46-46-76	40-40-40-84	38-38-38-78	28-36-36-76
Data Transfer Bandwidth	51,200 MB/s (PC5 51200)	51,200 MB/s (PC5-51200)	51,200 MB/s (PC5-51200)	51,200 MB/s (PC5-51200)	51,200 MB/s (PC5-51200)	51,200 MB/s (PC5-51200)	49,600 MB/s (PC5 49600)	48,000 MB/s (PC5 48000)
Voltage	1.35V	1.35V	1.4V	1.25V	1.35V	1.35V	1.25V	1.4V
Compatibility	Intel: 700 series							
Dimensions	46.1(H) x 144.2(L) x 7(W)mm							
Profile	8200 MHz↑ Intel XMP 3.0 8000 MHz↓ Intel XMP 3.0 / AMD EXPO							
Warranty	Lifetime warranty							

Module Type	DDR5 288 Pin Non-ECC Unbuffered DIMM						
Frequency	6000	6000	6000	6000	6000	6000	6000
Capacity	16GB 2x16GB	16GB 2x16GB	16GB 2x16GB	32GB 2x32GB	8GB 16GB 2x8GB 2x16GB	32GB 2x32GB	16GB 2x16GB
Latency	30-36-36-76	32-36-36-76	34-36-36-76	34-44-44-84	38-38-38-78	38-38-38-78	38-46-46-76
Data Transfer Bandwidth	48,000 MB/s (PC5 48000)	48,000 MB/s (PC5 48000)	48,000 MB/s (PC5 48000)	48,000 MB/s (PC5 48000)	48,000 MB/s (PC5 48000)	48,000 MB/s (PC5 48000)	48,000 MB/s (PC5 48000)
Voltage	1.35V	1.35V	1.35V	1.35V	1.25V	1.35V	1.25V
Compatibility	Intel: 700 series						
Dimensions	46.1(H) x 144.2(L) x 7(W)mm						
Profile	8200 MHz↑ Intel XMP 3.0 8000 MHz↓ Intel XMP 3.0 / AMD EXPO						
Warranty	Lifetime warranty						

T-FORCE

T-FORCE is TEAM force. The red "T" on the logo of "TF" represents TEAMGROUP's passion for the storage products. The black "F" represents TEAMGROUP's over 18 years of promotion of storage products. The visual design of the perfect combination elegantly symbolizes a pair of flying wings.

TEAM GROUP **TC T-CREATE**

PERFECT CHOICE
Products from Team Group Inc. have been well received by the technology media around the globe and have won honors such as COMPUTEX d&i awards, COMPUTEX Best Choice Award, GOOD DESIGN AWARD, Golden Pin Design Award, Taiwan Excellence Awards, iF Design Award and Red Dot Award.

GLOBALIZATION
Team Group Inc. has built up a strong center in Taiwan for production, R&D, sales and customer service, and has over 300 global sales agents and 400 employees worldwide. Team Group Inc. uses differentiating sales strategies with a global vision and localized channel management to establish a closed distribution network.

GUARANTEED QUALITY & WARRANTY SERVICE
Team Group Inc. is well praised by the industry and customers by adhering to the corporate philosophy of "Integrity, Innovation, Professionalism, Efficiency, Discipline, and Simplicity." We offer faster repair and exchange services than others, guaranteeing a minimized delivery time for every global customer.

SOLID R&D CAPABILITIES
With the best technical and manufacturing team, products from Team Group Inc. are made with innovation and strict quality control. Our memory technology has passed the ISO9001 and ISO14001 certifications, taking the lead in the memory industry with our latest overclocking memory modules.

3F., No.166, Jian 1st Rd., Zhonghe Dist.,New Taipei City 23511, Taiwan
Team Group Inc.
Tel: +886-2-82265000 Fax: +886-2-82265808
mail: sales@teamgroup.com.tw / rma@teamgroup.com.tw

FC CE UK CA CAN ICES-3(B)/NMB-3(B) RoHS COMPLIANT

Module Type	DDR5 288 Pin Non-ECC Unbuffered DIMM							
Frequency	6000	5600	5600	5600	5600	5600	5600	5200
Capacity	32GB 2x32GB	16GB 2x16GB	16GB 2x16GB	32GB 2x32GB	16GB 2x16GB 32GB 2x32GB	8GB 16GB 2x8GB 2x16GB	32GB 2x32GB	16GB 32GB 2x8GB 2x16GB 2x32GB
Latency	38-46-46-76	32-36-36-76	36-36-36-76	36-36-36-76	38-46-46-76	40-40-40-84	40-40-40-84	40-40-40-76
Data Transfer Bandwidth	48,000 MB/s (PC5 48000)	44,800 MB/s (PC5-44800)	44,800 MB/s (PC5-44800)	44,800 MB/s (PC5-44800)	44,800 MB/s (PC5-44800)	44,800 MB/s (PC5-44800)	44,800 MB/s (PC5-44800)	41,600 MB/s (PC5 48000)
Voltage	1.35V	1.2V	1.2V	1.3V	1.2V	1.2V	1.3V	1.25V
Compatibility	Intel: 700 series							
Dimensions	46.1(H) x 144.2(L) x 7(W)mm							
Profile	8200 MHz↑ Intel XMP 3.0 8000 MHz↓ Intel XMP 3.0 / AMD EXPO							
Warranty	Lifetime warranty							

※ The frequency and stability of the overclocking memory when automatic reading of the overclocking value (XMP or EXPO) is turned on will vary depending on the difference between the motherboard and CPU. Check "Product Compatibility Inquiry" before purchase for further info: https://www.teamgroupinc.com/en/support/compatibility.php

※ We reserve the right to modify product specifications without prior notice.

※ Before purchasing memory products, please refer to the QVL(Qualified Vendor List) compatibility list first of the motherboard.

※ The quality of the CPU memory controller (IMC) and the version from the BIOS of motherboard may both potentially affect the operating frequency of the memory.

※The overclocking memory with high frequency needs a more enhanced heat solution inside the case, to bring out better stability.

※Before purchasing memory products, please refer to the QVL(Qualified Vendor List) compatibility list first of the motherboard.

※The quality of the CPU memory controller (IMC) and the version from the BIOS of motherboard may both potentially affect the operating frequency of the memory.

※The overclocking memory with high frequency needs a more enhanced heat solution inside the case, to bring out better stability.

※Do not mix memory modules of different capacities, frequencies, brands, or models. Each memory kit is paired through compatibility testing. Mixing different kits may cause system instability or failure to boot.

※Memory kits labeled "Support Intel XMP 3.0" only include XMP Profiles. Kits labeled "Support AMD EXPO" only include EXPO Profiles. Kits labeled "COMBINATION Intel XMP/AMD EXPO" include both XMP and EXPO Profiles.

※If the system fails to boot, reset the motherboard CMOS, enter BIOS with default frequency, and then enable the Profile to retry system boot.

※Failure to install and use the memory as per the official specifications, warnings, or operating instructions may result in the memory not operating at the speed indicated on the packaging, system instability, or damage to other hardware.

※For product-related or technical support issues, please contact our professional technical support team via email.

Ordering information

Color	Frequency	CAS Latency/Voltage	Capacity	IC Specifications	Team P/N
BLACK	DDR5-5200 （PC5-41600）	CL40-40-40-76 1.25V	16GB	x8	FF3D516G5200HC40C01
			32GB	x8	FF3D532G5200HC40C01
	DDR5-5600 （PC5-44800）	CL32-36-36-76 1.2V	16GB	x8	FF3D516G5600HC3201
		CL36-36-36-76 1.2V	16GB	x8	FF3D516G5600HC36B01
		CL36-36-36-76 1.3V	32GB	x8	FF3D532G5600HC36B01
		CL38-46-46-76 1.2V	16GB	x8	FF3D516G5600HC38G01
			32GB	x8	FF3D532G5600HC38G01
		CL40-40-40-84 1.2V	8GB	x8	FF3D58G5600HC40B01
			16GB	x8	FF3D516G5600HC40B01
		CL40-40-40-84 1.3V	32GB	x8	FF3D532G5600HC40B01
	DDR5-6000 （PC5-48000）	CL28-36-36-76 1.4V	16GB	x8	FF3D516G6000HC28A01
		CL30-36-36-76 1.35V	16GB	x8	FF3D516G6000HC3001
		CL32-36-36-76 1.35V	16GB	x8	FF3D516G6000HC3201
		CL34-36-36-76 1.35V	16GB	x8	FF3D516G6000HC34C01
		CL34-44-44-84 1.35V	32GB	x8	FF3D532G6000HC34B01
		CL38-38-38-78 1.25V	8GB	x8	FF3D58G6000HC38A01
			16GB	x8	FF3D516G6000HC38A01
		CL38-38-38-78 1.35V	32GB	x8	FF3D532G6000HC38A01
		CL38-46-46-76 1.25V	16GB	x8	FF3D516G6000HC38G01
		CL38-46-46-76 1.35V	32GB	x8	FF3D532G6000HC38G01
	DDR5-6200 （PC5-49600）	CL38-38-38-78 1.25V	16GB	x8	FF3D516G6200HC38A01
	DDR5-6400 （PC5-51200）	CL30-39-39-76 1.35V	16GB	x8	FF3D516G6400HC30C01
		CL32-39-39-84 1.35V	16GB	x8	FF3D516G6400HC32A01
		CL34-39-39-76 1.35V	16GB	x8	FF3D516G6400HC34D01
		CL34-46-46-84 1.4V	32GB	x8	FF3D532G6400HC34E01
		CL40-40-40-84 1.35V	8GB	x8	FF3D58G6400HC40B01
			16GB	x8	FF3D516G6400HC40B01
	DDR5-7000 （PC5-56000）	CL32-42-42-84 1.4V	16GB	x8	FF3D516G7000HC32C01

T·FORCE

T-FORCE is TEAM force. The red "T" on the logo of "TF" represents TEAMGROUP's passion for the storage products. The black "F" represents TEAMGROUP's over 18 years of promotion of storage products. The visual design of the perfect combination elegantly symbolizes a pair of flying wings.

TEAM GROUP

TC T·CREATE

PERFECT CHOICE
Products from Team Group Inc. have been well received by the technology media around the globe and have won honors such as COMPUTEX d&i awards, COMPUTEX Best Choice Award, GOOD DESIGN AWARD, Golden Pin Design Award, Taiwan Excellence Awards, iF Design Award and Red Dot Award.

GLOBALIZATION
Team Group Inc. has built up a strong center in Taiwan for production, R&D, sales and customer service, and has over 300 global sales agents and 400 employees worldwide. Team Group Inc. uses differentiating sales strategies with a global vision and localized channel management to establish a closed distribution network.

GUARANTEED QUALITY & WARRANTY SERVICE
Team Group Inc. is well praised by the industry and customers by adhering to the corporate philosophy of "Integrity, Innovation, Professionalism, Efficiency, Discipline, and Simplicity." We offer faster repair and exchange services than others, guaranteeing a minimized delivery time for every global customer.

SOLID R&D CAPABILITIES
With the best technical and manufacturing team, products from Team Group Inc. are made with innovation and strict quality control. Our memory technology has passed the ISO9001 and ISO14001 certifications, taking the lead in the memory industry with our latest overclocking memory modules.

3F., No.166, Jian 1st Rd., Zhonghe Dist.,New Taipei City 23511, Taiwan
Team Group Inc.
Tel: +886-2-82265000 Fax: +886-2-82265808
mail: sales@teamgroup.com.tw / rma@teamgroup.com.tw

FC CE UK CA RoHS COMPLIANT
CAN ICES-3(B)/NMB-3(B)

Ordering information

Color	Frequency	CAS Latency/Voltage	Capacity	IC Specifications	Team P/N
WHITE	DDR5-5200 （PC5-41600）	CL40-40-40-76 1.25V	16GB	x8	FF4D516G5200HC40C01
			32GB	x8	FF4D532G5200HC40C01
	DDR5-5600 （PC5-44800）	CL32-36-36-76 1.2V	16GB	x8	FF4D516G5600HC3201
		CL36-36-36-76 1.2V	16GB	x8	FF4D516G5600HC36B01
		CL36-36-36-76 1.3V	32GB	x8	FF4D532G5600HC36B01
		CL38-46-46-76 1.2V	16GB	x8	FF4D516G5600HC38G01
			32GB	x8	FF4D532G5600HC38G01
		CL40-40-40-84 1.2V	8GB	x8	FF4D58G5600HC40B01
			16GB	x8	FF4D516G5600HC40B01
		CL40-40-40-84 1.3V	32GB	x8	FF4D532G5600HC40B01
	DDR5-6000 （PC5-48000）	CL28-36-36-76 1.4V	16GB	x8	FF4D516G6000HC28A01
		CL30-36-36-76 1.35V	16GB	x8	FF4D516G6000HC3001
		CL32-36-36-76 1.35V	16GB	x8	FF4D516G6000HC3201
		CL34-36-36-76 1.35V	16GB	x8	FF4D516G6000HC34C01
		CL34-44-44-84 1.35V	32GB	x8	FF4D532G6000HC34B01
		CL38-38-38-78 1.25V	8GB	x8	FF4D58G6000HC38A01
			16GB	x8	FF4D516G6000HC38A01
		CL38-38-38-78 1.35V	32GB	x8	FF4D532G6000HC38A01
		CL38-46-46-76 1.25V	16GB	x8	FF4D516G6000HC38G01
		CL38-46-46-76 1.35V	32GB	x8	FF4D532G6000HC38G01
	DDR5-6200 （PC5-49600）	CL38-38-38-78 1.25V	16GB	x8	FF4D516G6200HC38A01
	DDR5-6400 （PC5-51200）	CL30-39-39-76 1.35V	16GB	x8	FF4D516G6400HC30C01
		CL32-39-39-84 1.35V	16GB	x8	FF4D516G6400HC32A01
		CL34-39-39-76 1.35V	16GB	x8	FF4D516G6400HC34D01
		CL34-46-46-84 1.4V	32GB	x8	FF4D532G6400HC34E01
		CL40-40-40-84 1.35V	8GB	x8	FF4D58G6400HC40B01
			16GB	x8	FF4D516G6400HC40B01
	DDR5-7000 （PC5-56000）	CL32-42-42-84 1.4V	16GB	x8	FF4D516G7000HC32C01

Ordering information

Color	Frequency	CAS Latency/Voltage	Capacity	IC Specifications	Team P/N
BLACK	DDR5-5200（PC5-41600）	CL40-40-40-76 1.25V	2x8GB	x8	FF3D516G5200HC40CDC01
			2x16GB	x8	FF3D532G5200HC40CDC01
			2x32GB	x8	FF3D564G5200HC40CDC01
	DDR5-5600（PC5-44800）	CL32-36-36-76 1.2V	2x16GB	x8	FF3D532G5600HC32DC01
		CL36-36-36-76 1.2V	2x16GB	x8	FF3D532G5600HC36BDC01
		CL36-36-36-76 1.3V	2x32GB	x8	FF3D564G5600HC36BDC01
		CL38-46-46-76 1.2V	2x16GB	x8	FF3D532G5600HC38GDC01
			2x32GB	x8	FF3D564G5600HC38GDC01
		CL40-40-40-84 1.2V	2x8GB	x8	FF3D516G5600HC40BDC01
			2x16GB	x8	FF3D532G5600HC40BDC01
		CL40-40-40-84 1.3V	2x32GB	x8	FF3D564G5600HC40BDC01
	DDR5-6000（PC5-48000）	CL28-36-36-76 1.4V	2x16GB	x8	FF3D532G6000HC28ADC01
		CL30-36-36-76 1.35V	2x16GB	x8	FF3D532G6000HC30DC01
		CL32-36-36-76 1.35V	2x16GB	x8	FF3D532G6000HC32DC01
		CL34-36-36-76 1.35V	2x16GB	x8	FF3D532G6000HC34CDC01
		CL34-44-44-84 1.35V	2x32GB	x8	FF3D564G6000HC34BDC01
		CL38-38-38-78 1.25V	2x8GB	x8	FF3D516G6000HC38ADC01
			2x16GB	x8	FF3D532G6000HC38ADC01
		CL38-38-38-78 1.35V	2x32GB	x8	FF3D564G6000HC38ADC01
		CL38-46-46-76 1.25V	2x16GB	x8	FF3D532G6000HC38GDC01
		CL38-46-46-76 1.35V	2x32GB	x8	FF3D564G6000HC38GDC01
	DDR5-6200（PC5-49600）	CL38-38-38-78 1.25V	2x16GB	x8	FF3D532G6200HC38ADC01
	DDR5-6400（PC5-51200）	CL30-39-39-76 1.35V	2x16GB	x8	FF3D532G6400HC30CDC01
		CL32-39-39-84 1.35V	2x16GB	x8	FF3D532G6400HC32ADC01
			2x24GB	x8	FF3D548G6400HC32ADC01
		CL32-39-39-84 1.4V	2x48GB	x8	FF3D596G6400HC32ADC01
		CL34-39-39-76 1.35V	2x16GB	x8	FF3D532G6400HC34DDC01
		CL34-44-44-84 1.35V	2x32GB	x8	FF3D564G6400HC34BDC01
		CL34-46-46-84 1.4V	2x32GB	x8	FF3D564G6400HC34EDC01
		CL38-46-46-76 1.25V	2x16GB	x8	FF3D532G6400HC38GDC01
		CL38-46-46-76 1.35V	2x16GB	x8	FF3D532G6400HC38GDC01
		CL40-40-40-84 1.35V	2x8GB	x8	FF3D516G6400HC40BDC01
			2x16GB	x8	FF3D532G6400HC40BDC01
	DDR5-6600（PC5-52800）	CL34-40-40-84 1.4V	2x16GB	x8	FF3D532G6600HC34DC01
	DDR5-6800（PC5-54400）	CL34-44-44-84 1.4V	2x16GB	x8	FF3D532G6800HC34BDC01
		CL36-46-46-84 1.4V	2x48GB	x8	FF3D596G6800HC36DDC01
	DDR5-7000（PC5-56000）	CL32-42-42-84 1.4V	2x16GB	x8	FF3D532G7000HC32CDC01
		CL34-42-42-84 1.4V	2x16GB	x8	FF3D532G7000HC34ADC01
			2x48GB	x8	FF3D596G7000HC34ADC01
	DDR5-7200（PC5-57600）	CL34-42-42-84 1.4V	2x16GB	x8	FF3D532G7200HC34ADC01
			2x24GB	x8	FF3D548G7200HC34ADC01
	DDR5-7600（PC5-60800）	CL36-46-46-84 1.4V	2x16GB	x8	FF3D532G7600HC36DDC01
		CL36-47-47-84 1.4V	2x24GB	x8	FF3D548G7600HC36EDC01
	DDR5-7800（PC5-62400）	CL38-48-48-84 1.4V	2x16GB	x8	FF3D532G7800HC38DDC01
	DDR5-8000（PC5-64000）	CL38-48-48-84 1.45V	2x16GB	x8	FF3D532G8000HC38DDC01
		CL38-49-49-84 1.4V	2x24GB	x8	FF3D548G8000HC38EDC01
	DDR5-8200（PC5-65600）	CL38-49-49-84 1.4V	2x24GB	x8	FF3D548G8200HC38EDC01

T·FORCE

T-FORCE is TEAM force. The red "T" on the logo of "TF" represents TEAMGROUP's passion for the storage products. The black "F" represents TEAMGROUP's over 18 years of promotion of storage products. The visual design of the perfect combination elegantly symbolizes a pair of flying wings.

TEAM GROUP

TC T·CREATE

PERFECT CHOICE
Products from Team Group Inc. have been well received by the technology media around the globe and have won honors such as COMPUTEX d&i awards, COMPUTEX Best Choice Award, GOOD DESIGN AWARD, Golden Pin Design Award, Taiwan Excellence Awards, iF Design Award and Red Dot Award.

GLOBALIZATION
Team Group Inc. has built up a strong center in Taiwan for production, R&D, sales and customer service, and has over 300 global sales agents and 400 employees worldwide. Team Group Inc. uses differentiating sales strategies with a global vision and localized channel management to establish a closed distribution network.

GUARANTEED QUALITY & WARRANTY SERVICE
Team Group Inc. is well praised by the industry and customers by adhering to the corporate philosophy of "Integrity, Innovation, Professionalism, Efficiency, Discipline, and Simplicity." We offer faster repair and exchange services than others, guaranteeing a minimized delivery time for every global customer.

SOLID R&D CAPABILITIES
With the best technical and manufacturing team, products from Team Group Inc. are made with innovation and strict quality control. Our memory technology has passed the ISO9001 and ISO14001 certifications, taking the lead in the memory industry with our latest overclocking memory modules.

3F., No.166, Jian 1st Rd., Zhonghe Dist.,New Taipei City 23511, Taiwan
Team Group Inc.
Tel: +886-2-82265000 Fax: +886-2-82265808
mail: sales@teamgroup.com.tw / rma@teamgroup.com.tw

FC CE UKCA CAN ICES-3(B)/NMB-3(B) RoHS COMPLIANT

Ordering information

Color	Frequency	CAS Latency/Voltage	Capacity	IC Specifications	Team P/N
WHITE	DDR5-5200 （PC5-41600）	CL40-40-40-76 1.25V	2x8GB	x8	FF4D516G5200HC40CDC01
			2x16GB	x8	FF4D532G5200HC40CDC01
			2x32GB	x8	FF4D564G5200HC40CDC01
	DDR5-5600 （PC5-44800）	CL32-36-36-76 1.2V	2x16GB	x8	FF4D532G5600HC32DC01
		CL36-36-36-76 1.2V	2x16GB	x8	FF4D532G5600HC36BDC01
		CL36-36-36-76 1.3V	2x32GB	x8	FF4D564G5600HC36BDC01
		CL38-46-46-76 1.2V	2x16GB	x8	FF4D532G5600HC38GDC01
			2x32GB	x8	FF4D564G5600HC38GDC01
		CL40-40-40-84 1.2V	2x8GB	x8	FF4D516G5600HC40BDC01
			2x16GB	x8	FF4D532G5600HC40BDC01
		CL40-40-40-84 1.3V	2x32GB	x8	FF4D564G5600HC40BDC01
	DDR5-6000 （PC5-48000）	CL28-36-36-76 1.4V	2x16GB	x8	FF4D532G6000HC28ADC01
		CL30-36-36-76 1.35V	2x16GB	x8	FF4D532G6000HC30DC01
		CL32-36-36-76 1.35V	2x16GB	x8	FF4D532G6000HC32DC01
		CL34-36-36-76 1.35V	2x16GB	x8	FF4D532G6000HC34CDC01
		CL34-44-44-84 1.35V	2x32GB	x8	FF4D564G6000HC34BDC01
		CL38-38-38-78 1.25V	2x8GB	x8	FF4D516G6000HC38ADC01
			2x16GB	x8	FF4D532G6000HC38ADC01
		CL38-38-38-78 1.35V	2x32GB	x8	FF4D564G6000HC38ADC01
		CL38-46-46-76 1.25V	2x16GB	x8	FF4D532G6000HC38GDC01
		CL38-46-46-76 1.35V	2x32GB	x8	FF4D564G6000HC38GDC01
	DDR5-6200 （PC5-49600）	CL38-38-38-78 1.25V	2x16GB	x8	FF4D532G6200HC38ADC01
	DDR5-6400 （PC5-51200）	CL30-39-39-76 1.35V	2x16GB	x8	FF4D532G6400HC30CDC01
		CL32-39-39-84 1.35V	2x16GB	x8	FF4D532G6400HC32ADC01
			2x24GB	x8	FF4D548G6400HC32ADC01
		CL32-39-39-84 1.4V	2x48GB	x8	FF4D596G6400HC32ADC01
		CL34-39-39-76 1.35V	2x16GB	x8	FF4D532G6400HC34DDC01
		CL34-44-44-84 1.35V	2x32GB	x8	FF4D564G6400HC34BDC01
		CL34-46-46-84 1.4V	2x32GB	x8	FF4D564G6400HC34EDC01
		CL38-46-46-76 1.25V	2x16GB	x8	FF4D532G6400HC38GDC01
		CL38-46-46-76 1.35V	2x16GB	x8	FF4D532G6400HC38GDC01
		CL40-40-40-84 1.35V	2x8GB	x8	FF4D516G6400HC40BDC01
			2x16GB	x8	FF4D532G6400HC40BDC01
	DDR5-6600 （PC5-52800）	CL34-40-40-84 1.4V	2x16GB	x8	FF4D532G6600HC34DC01
	DDR5-6800 （PC5-54400）	CL34-44-44-84 1.4V	2x16GB	x8	FF4D532G6800HC34BDC01
		CL36-46-46-84 1.4V	2x48GB	x8	FF4D596G6800HC36DDC01
	DDR5-7000 （PC5-56000）	CL32-42-42-84 1.4V	2x16GB	x8	FF4D532G7000HC32CDC01
		CL34-42-42-84 1.4V	2x16GB	x8	FF4D532G7000HC34ADC01
			2x48GB	x8	FF4D596G7000HC34ADC01
	DDR5-7200 （PC5-57600）	CL34-42-42-84 1.4V	2x16GB	x8	FF4D532G7200HC34ADC01
			2x24GB	x8	FF4D548G7200HC34ADC01
	DDR5-7600 （PC5-60800）	CL36-46-46-84 1.4V	2x16GB	x8	FF4D532G7600HC36DDC01
		CL36-47-47-84 1.4V	2x24GB	x8	FF4D548G7600HC36EDC01
	DDR5-7800 （PC5-62400）	CL38-48-48-84 1.4V	2x16GB	x8	FF4D532G7800HC38DDC01
	DDR5-8000 （PC5-64000）	CL38-48-48-84 1.45V	2x16GB	x8	FF4D532G8000HC38DDC01
		CL38-49-49-84 1.4V	2x24GB	x8	FF4D548G8000HC38EDC01
	DDR5-8200 （PC5-65600）	CL38-49-49-84 1.4V	2x24GB	x8	FF4D548G8200HC38EDC01

T·FORCE

T-FORCE is TEAM force. The red "T" on the logo of "TF" represents TEAMGROUP's passion for the storage products. The black "F" represents TEAMGROUP's over 18 years of promotion of storage products. The visual design of the perfect combination elegantly symbolizes a pair of flying wings.

TEAM GROUP　**TC T·CREATE**

PERFECT CHOICE

Products from Team Group Inc. have been well received by the technology media around the globe and have won honors such as COMPUTEX d&i awards, COMPUTEX Best Choice Award, GOOD DESIGN AWARD, Golden Pin Design Award, Taiwan Excellence Awards, iF Design Award and Red Dot Award.

GLOBALIZATION

Team Group Inc. has built up a strong center in Taiwan for production, R&D, sales and customer service, and has over 300 global sales agents and 400 employees worldwide. Team Group Inc. uses differentiating sales strategies with a global vision and localized channel management to establish a closed distribution network.

GUARANTEED QUALITY & WARRANTY SERVICE

Team Group Inc. is well praised by the industry and customers by adhering to the corporate philosophy of "Integrity, Innovation, Professionalism, Efficiency, Discipline, and Simplicity." We offer faster repair and exchange services than others, guaranteeing a minimized delivery time for every global customer.

SOLID R&D CAPABILITIES

With the best technical and manufacturing team, products from Team Group Inc. are made with innovation and strict quality control. Our memory technology has passed the ISO9001 and ISO14001 certifications, taking the lead in the memory industry with our latest overclocking memory modules.

FC CE UKCA CAN ICES-3(B)/NMB-3(B) RoHS COMPLIANT