

## Safety shower - wall mounted for indoor use

### COMPLIANCE

EN 15154-1, NF X 15-221

### ADVANTAGES

- ISO 3864 compliant
- EN 15154-1 and NF X 15-221 compliant
- First-aid in case of chemical projection

### BUT ALSO...

- EN 15154-1 compliant
- Delivered with the first-aid labelling
- Compliant to the article R. 4224-14 of the Labour Code



### TECHNICAL FEATURES

Model	<b>DS24</b>	Shower head	<b>Green ABS RAL 6032</b>
Compliance	<b>EN 15154-1, NF X 15-221</b>	Pipe	<b>4.00 galvanised steel + grey epoxy painted RAL 7040</b>
Shipping dimensions HxWxD (mm)	<b>420 x 120 x 380</b>	Water inlet	<b>F 1"</b>
Use	<b>internal use</b>	HS Code	<b>73242921</b>
Setting	<b>handle operating</b>		
	<b>wall mounted</b>		

### OPTIONS

- Thermostatic mixing valve for safety shower and combination unit (Réf : MTD)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Eye-washer flow (L/min)	Shower flow (L/min)	Weight (kg)
DS24			0	90	4.00