

Recirculating air box Labopur - NF X 15-211

COMPLIANCE

CE

ADVANTAGES

- CE certified
- NF X 15-211 compliant
- Storage of flammables, corrosives and toxics

BUT ALSO...

- Active coal filters adsorption capacity and filtration system certified NF X 15-211
- Fan in compliance with CE specifications
- Suitable on any safety cabinet
- No modification of building's structure required
- Easy and aesthetic installation
- Lighting control allowing to survey the proper working of the fan
- Front control window to see immediately the filter
- Active coal filter tested to the standard NF X 15-211
- Stop 99,97% of the particles with a diameter bigger than 0.3 µm
- Easy replacement of the active coal filter



TECHNICAL FEATURES

Model	H50C	Electrical power (W)	15.00
Compliance	CE	Sound power of the fan dB(A)	20
Shipping dimensions HxWxD (mm)	700 x 500 x 500	HS Code	43.00
Voltage (volts)	220-240 volts monophase		84146000
Flow (m ³ /h)	86		

COMPLEMENTARY PRODUCTS

- Activated carbon filter for ammonia vapors - for filtration box H50C (or old cabinets range 12 before 2002) (Réf : AMM50)
- Clamp collar - diameter 100 mm (Réf : CDS100)
- Connection sleeve - diameter 100 mm (Réf : CHJ)
- Activated carbon filter for organic and corrosive vapors - for filtration box H50C (or old cabinets range 12.X before 2002) (Réf : CORG51)
- Activated carbon filter for formaldehyde vapors - for filtration box H50C (or old cabinets range 12.X before 2002) (Réf : FOR50)
- Flexible sleeve in PVC - 1 meter (Réf : KL100)
- Connecting kit (Réf : KRC)
- Activated carbon filter for organic vapors - for filtration box H50C (or old cabinets range 12.X before 2002) (Réf : ORG50)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Weight (kg)
H50C	310 x 505 x 485		15.00